

Lithium-Ion Battery Landscape



Catalog #	DCB122	DCB124	DCB126	DCBP034	DCB203	DCB230	DCBP320	DCB240	DCB2104	DCB205	DCBP520	DCB206	DCB208	DCB2108	DCB210	DCB606	DCB609	DCB612	DCB615
Image																			
System	12V MAX	12V MAX	12V MAX	POWERSTACK	20V MAX	20V MAX	POWERSTACK	20V MAX	POWERPACK	20V MAX	POWERSTACK	20V MAX	20V MAX	POWERPACK	20V MAX	FLEXVOLT	FLEXVOLT	FLEXVOLT	FLEXVOLT
Capacity (Ah)	2.0	3.0	5.0	1.7	2.0	3.0	3.5	4.0	4.0	5.0	5.0	6.0	8.0	8.0	10.0	6.0	9.0	12.0	15.0
Watt Hours	24	36	60	34	40	60	70	80	80	100	100	120	160	160	200	120	180	240	300
Fuel Gauge	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Max Charge Rate	4A	4A	4A	4A	4A	4A	8A	4A	4A	8A	8A	8A	8A	8A	8A	12A	12A	12A	12A
Warranty	2 Years	2 Years	2 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years
Weight (lbs.)	0.5	0.5	0.9	0.7	0.8	1.1	1.19	1.1	1.1	1.4	1.6	1.9	1.9	1.9	2.0	2.4	3.2	3.2	4.5
Shipping	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Class 9	Class 9	Class 9	Class 9	Standard*	Standard*	Standard*	Standard*
Kit Suffix	F	G	J	E	D	L	S	Q	QQ	P	H	R	W	WW	U	T	X	Y	Z
Cells	18mm	18mm	18mm	Pouch	18mm	21mm	Pouch	21mm	21mm Tabless	18mm	Pouch	21mm	21mm	21mm Tabless	18mm	18mm	21mm	21mm	21mm

Battery Shipping

- Batteries up to 100 Watt Hours can be shipped ground with proper packaging and labeling, no Class 9 designation necessary.

*standard shipping only if transport cap attached.



- When shipping via air, up to 3 batteries (no more than 100 Watt Hours each) may be shipped together without a Class 9 designation only if a tool is included in the box. The included tool must fit the batteries.
- If no tool is included, any battery shipped by itself via air must be designated Class 9 (special training, certification, and packaging required.)

Questions? Contact batteries@sbdinc.com for more information.

Lithium-Ion Charger Landscape



Catalog #	DCB1104	DCB115	DCB1106	DCB118	DCB1112	DCB094K	DCB102	DCB104
Image								
Design	Desktop	Desktop	Desktop	Desktop	Desktop	Compact USB	Dual-Port USB	Four-Port ToughSystem
Two-Stage Indicator	Yes	No	Yes	No	Yes	Yes	No	No
Systems	12V MAX 20V MAX FLEXVOLT	12V MAX 20V MAX FLEXVOLT	12V MAX 20V MAX FLEXVOLT	20V MAX FLEXVOLT	20V MAX FLEXVOLT	20V MAX FLEXVOLT	12V MAX 20V MAX FLEXVOLT	12V MAX 20V MAX FLEXVOLT
# of Charging Ports	1	1	1	1	1	1	2	4
Max Rate (A)	4.00	4.00	6.00	8.00	12.00	5.00	4.00	8.00
Charging Method							Simultaneous	Simultaneous

• DCB1104 replaces DCB115 in tool kits

- Max Charge Rate for 12V MAX Batteries: 4 Amps
- Max Charge Rate for 20V MAX Compact (1P) Batteries: 4 Amps
 - Except DCBP520, which has 8A max rate
- Max Charge Rate for 20V MAX XR (2P) Batteries: 8 Amps
- Max Charge Rate for FLEXVOLT (3P) Batteries: 12 Amps