



KING CANADA

GENERATOR LINEUP



| MODEL | KCG-1501GX | KCG-2001i | KCG-3800i-DF | KCG-5000i-DF | KCG-5100G | KCG-5101GE-DF | KCG-6502GE | KCG-10001GE | KCG-10002GE-TF | KCG-11000i-TF | KCG-12000GE | KCG-12001GE-DF | KCG-15000GE |
|------------------------------------|---------------------------|--|---|---|--|---|---|--|--|--|--|--|---|
| DESCRIPTION | 1,800W Gasoline Generator | 2,000W Gasoline Digital Inverter Generator | 3,800W Dual Fuel Gasoline/ Propane Digital Inverter Generator | 5,000W Dual Fuel Gasoline/ Propane Digital Inverter Generator | 5,100W Gasoline Generator With Wheel Kit | 5,100W Dual Fuel Gasoline / Propane Generator with Electric Start | 6,500W Gasoline Generator With Electric Start | 10,000W Gasoline Generator With Electric Start | 10,000W TRI-Fuel Generator With Electric Start | 11,000W Tri- Fuel Digital Inverter Generator | 12,000W Gasoline Generator With Electric Start | 12,000W Dual Fuel Gasoline / Propane Generator With Electric Start | 15,000W V-Twin Gasoline Generator With Electric Start |
| PEAK WATTAGE (STARTING) | 1,800W | 2,000W | 3,800W | 5,000W | 5,100W | 5,100W | 6,500W | 10,000W | 10,000W | 11,000W | 12,000W | 12,000W | 15,000W |
| RUNNING WATTAGE (GASOLINE) | 1,400W | 1,600W | 3,000W | 3,700W | 4,000W | 4,000W | 5,000W | 7,500W | 7,500W | 8,200W | 9,000W | 9,000W | 12,500W |
| RUNNING WATTAGE (PROPANE) | - | - | 2,700W | 3,330W | - | 3,600W | - | - | 6,700W | 7,380W | - | 8,100W | - |
| RUNNING WATTAGE (NATURAL GAS) | - | - | - | - | - | - | - | - | 5,600W | 6,150W | - | - | - |
| CONTROL PANELS | | | | | | | | | | | | | |
| DC OUTPUT | 12V (DC 8A) | 12V (DC 8A) | 12V (DC 8A) | 12V (DC 8A) | - | - | - | - | - | - | - | - | - |
| ENGINE (OHV) | 3 HP | 3 HP | 5 HP | 8 HP | 8 HP | 8 HP | 10 HP | 15 HP | 15 HP | 18 HP | 18 HP | 18 HP | 20 HP |
| NO LOAD SPEED | 3,600 RPM | 4,800 RPM | 3,300 RPM | 3,600 RPM | 3,600 RPM | 3,750 RPM | 3,750 RPM | 3,600 RPM | 3,600 RPM | 3,600 RPM | 3,750 RPM | 3,750 RPM | 3,600 RPM |
| DISPLACEMENT (CC) | 98 | 80 | 141 | 224 | 224 | 224 | 274 | 420 | 420 | 457 | 457 | 457 | 713 |
| FUEL | Unleaded Gasoline | Unleaded Gasoline | Unleaded Gasoline & Propane | Unleaded Gasoline & Propane | Unleaded Gasoline | Unleaded Gasoline | Unleaded Gasoline | Unleaded Gasoline | Gasoline / LPG/ Natural Gas | Gasoline / LPG/ Natural Gas | Unleaded Gasoline | Unleaded Gasoline & Propane | Unleaded Gasoline |
| FUEL TANK (L) | 7 | 4.5 | 6.3 | 12 | 15 | 15 | 20 | 25 | 25 | 27 | 31 | 31 | 40 |
| OIL CAPACITY (L) | 0.5 | 0.35 | 0.4 | 0.6 | 0.6 | 0.6 | 0.7 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.6 |
| RUN TIME (GAS) (50%/25% LOAD) | 9 / 14 hrs | 8 / 12 hrs | 8 / 12 hrs | 10.5 / 18 hrs | 10 / 14 hrs | 10 / 14 hrs | 11 / 14.5 hrs | 11 / 17 hrs | 11 / 17 hrs | 10.5 / 17 hrs | 8.5 / 14 hrs | 8.5 / 14 hrs | 11 / 18 hrs |
| RUN TIME (LPG / NG) (50%/25% LOAD) | - | - | 10 / 17 hrs | 9.8 / 14 hrs | - | 10.5 / 16.5 hrs | - | - | - | 9.8 hrs / 14 hrs | - | 7 / 12 hrs | - |
| TOTAL HARMONIC DISTORTION (THD%) | ≤ 23% | ≤ 3% | ≤ 3% | ≤ 3% | ≤ 23% | ≤ 23% | ≤ 23% | ≤ 23% | ≤ 23% | ≤ 3% | ≤ 23% | ≤ 23% | ≤ 23% |
| NOISE LEVEL | 66 dB(A) | 61 dB(A) | 65 dB(A) | 65 dB(A) | 75 dB(A) | 75 dB(A) | 75 dB(A) | 73 dB(A) | 73 dB(A) | 68 dB(A) | 74 dB(A) | 74 dB(A) | 77 dB(A) |
| WEIGHT | 56 lbs | 48 lbs | 62 lbs | 110 lbs | 107 lbs | 118 lbs | 130 lbs | 195 lbs | 195 lbs | 210 lbs | 250 lbs | 255 lbs | 338 lbs |