


FIBERGLASS SERIES

6' FIBERGLASS BAKER SCAFFOLD WITH TRAP DOOR


- Non-conductive fiberglass, ideal for electrical work
- Durable and corrosion-resistant
- Lightweight platform with secure access trap door
- Designed to fit through standard door frames
- Enhanced safety with high-visibility green color
- Compact storage

METALTECH®



6' FIBERGLASS
BAKER SCAFFOLD
WITH TRAP DOOR

6' Fiberglass Baker scaffold with aluminum rungs and a 60 lb platform made of honeycomb polymer with an access trap door and capable of supporting up to 900 lb.



SAFECLIMB

SECURE ACCESS PLATFORM TRAP DOOR WITH LOCKING SYSTEM AND OPENING LIMITER



ANTI-SLIP POLYMER PLATFORM WITH 6063-T5 AEROSPACE-GRADE ALUMINUM FRAME



DESIGN: HIGH-VISIBILITY GREEN FOR BETTER VISIBILITY ON JOBSITE



5" NON-MARKING CASTERS WITH DOUBLE LOCK



ERGONOMIC HANDLES WITH LOCK INDICATOR

BUILD A TOWER - ADD A GUARDRAIL & OUTRIGGERS



GUARDRAILS SYSTEM*



SET OF 14" OUTRIGGERS*



SET OF 46" OUTRIGGERS*



STACKABLE UP TO 18'

6' FIBERGLASS BAKER SCAFFOLD WITH TRAP DOOR			
ASSEMBLED DIMENSIONS (WxDxH)	75.75 X 29.75 X 74 IN. (192.4 X 75.6 X 188 CM)	PLATFORM	ANTI-SLIP POLYMER PLATFORM WITH 6063-T5 AEROSPACE-GRADE ALUMINUM FRAME WITH TRAPDOOR
PACKAGE DIMENSIONS (WxDxH)	75.5 X 30.5 X 6.75 IN. (192.4 X 78.1 X 17.2 CM)	CASTERS	5 IN. (13 CM) DOUBLE LOCKING
WEIGHT	84.5 LB (38.3 KG)	STANDARDS	ANSI, CSA AND OSHA
LOAD CAPACITY	900 LB (408 KG). COMBINED WEIGHT OF USER + MATERIALS	MODEL	I-CFISC
WORKING HEIGHTS	FROM 27 TO 73 IN. (68.6 TO 185 CM) 2 IN. (5 CM) INCREMENT ADJUSTABLE HEIGHTS	UPC	778300009930
REACH	12 FT (3.7 M). STACKABLE UP TO 3 UNITS HIGH FOR 24 FT (7.4 M) REACH*	*Stacking units requires the use of outriggers and guardrails.	