



GVX Series Abrasive Blasting Respirator Tech Specifications

Respirator Type	Continuous flow airline respirator for use with high pressure compressed air or low pressure compressed air ambient air pumps
Components	• Helmet • Breathing Tubes • Capes • Flow Control Devices • Airline Hoses • Fittings • Lenses • Belts • Accessories
Approvals	• NIOSH Approved Type C and CE, Continuous Flow Class • ANSI/ISEA Z89.1, Type I, Class C Head Protection • ANSI/ISEA Z87.1, Z87+ High-Impact Face Protection • 1,000 Assigned Protection Factor (APF) with third-party testing per 29 CFR 1910.134
Specific Features	• Compatible for use with various Bullard air filtration and CO monitoring products for high pressure compressed air. • Manufactured in the USA with Domestic and Globally Sourced Materials
Helmet	• Removable and launderable comfort padding kit • Available in 4 distinct colors: Navy, Yellow, Red, Green • Weight: 2.6 pounds (helmet, suspension, lenses, comfort pad and cheek pads) • No OSHA-mandatory fit testing required to use the GVX respirator system. • Center mounted breathing tube connection to helmet • Lightweight adjustable 6-pt. Flex-Gear® ratchet suspension with 1" wide webbing, fits head sizes 6.5-8 • Replaceable breathing tube connection on the GVX helmet • "Grit Guard" visor to help prevent debris in-between lenses • Removable, adjustable cheek pads for increased stability • Non-porous shell allows for easy cleaning • Replaceable Inner lens made out of Tritan™ .040" thick PETG polymer • Viewable area of approx. 9.75" wide x 4" tall • Replaceable outer lens available in .015" or .040" thick PETG polymer • Optional adhesive-backed Mylar® Lens Covers • Tinted lenses available in green or smoke color • Optional Tear Off Lens Covers
Capes	• Double lining above the neck for additional durability and protection • Sewn-in knitted neck cuff provides snug, comfortable protection barrier to airborne contaminants while helping maintain positive pressure within the helmet • Four(4) Nylon cape styles available in 28" and 38" length with over the shoulder sleeves • Full length Hibernian parka available in 38" length with long sleeves • Made from 8 oz. Nylon Denier • Seal type on cape to helmet is a continuous steel cable sewn inside the cape fabric, itself. • Industrial or machine washable
Climate Control	• Optional climate control assembly (HC2400) available to cool or warm incoming air up to 30 degrees. (High Pressure Compressed Air Only) • Cool Tubes capable of supplying cooler air to the worker. High Pressure Compressed Air (AC1000) gives up to 30 degrees of cooling (High Pressure Compressed Air Only) • All climate control tubes are constructed of metal and molded plastic for increased durability • Cool Vest (DC70) available using a DC5040 Cool Tube and the same airline. Vest available in three sizes – medium/large or XL/XXL or 5X. (High Pressure Compressed Air Only)





GVX Series Abrasive Blasting Respirator Tech Specifications

Breathing Tube Assembly with Flow Control Device

- Available with continuous flow control device with 1/2" Industrial Interchange quick disconnect coupler for low pressure ambient air pumps
- Available with continuous flow control device with 1/4" quick disconnect coupler for high pressure compressed air
 - Industrial Interchange in steel, brass or stainless steel
 - Snap-Tite in steel, brass or stainless steel
 - CEJN in steel

Airline Hose

- Approved for use with 25-300 feet of airline hose depending on your configuration for high pressure compressed air
- Approved for use with 50-300 feet of airline hose for low pressure ambient air pumps
- Choice of EPDM-reinforced rubber 3/8" I.D. hose for high pressure compressed air or 1/2" I.D. hose for low pressure ambient air pumps
- Offers 1/2" industrial interchange connectors for low pressure ambient air pumps
- Offers 1/4" approved quick disconnect couplers compatible with breathing tube fittings for high pressure compressed air
 - Industrial Interchange in steel, brass or stainless steel
 - Snap-Tite in steel, brass or stainless steel
 - CEJN in steel

Warranty

2-year warranty that the GVX helmet will be free of defects in material and workmanship under normal use and service as a blast helmet. Capes, breathing tubes, and other disposable accessories not included. See the GVX Series Respirator User Manual for complete details.

Bullard Center

2421 Fortune Drive
Lexington, KY 40509 • USA
877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-246-0243

Americas Operations

1898 Safety Way
Cynthiana, KY 41031 • USA
877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-234-8987

Bullard GmbH

Dieselstrasse 8a
53424 Remagen • Germany
Tel: +49-2642 999980
Fax: +49-2642 9999829

Bullard Asia Pacific Pte. Ltd.

51 Changi Business Park Central 2
#03-04 The Signature
Singapore 486066
Tel: +65 6745 0556

©2025 Bullard. All rights reserved.
Flex-Gear and Free-Air
are registered trademarks of Bullard.
Tritan is a trademark of Eastman.
Mylar is a registered trademark of Dupont
Teijin Films.

